

ATF AL4



LOREX ATF AL4 is a synthetic high-performance lubricant for automatic transmissions. This product is fully backwards compatible with the older DEXRON specifications (III-H, III-G, III or II-D). As well as, it is developed with a high level of wear protection and an optimized level of friction for use in all common 4 and 5-speed automatic transmissions specially for CITROEN & PEUGEOT AND RENAULT.

RECOMMENDATIONS

ATF LT 71141
ATF DEXRON III-H
PEUGEOT/CITROËN B71 2340
RENUALT DPO (RENUALTMATIC D3)
ZF TE-ML 04D/ 11B/ 14B/ 17C



CERTIFICATE OF ANALYSIS

TEST	METHODS	SPECIFICATIONS	RESULT	UNITS
Appearance	Visual	Clear	Clear	-
Color	ASTM D1500	Yellow	Yellow	-
Density @ 15°C	ASTM D4052	0.84-0.86	0.855	g/cm ³
Kinematic Viscosity @ 40°C	ASTM D445	28.0 - 34.0	33	cSt
Kinematic Viscosity @ 100°C	ASTM D445	6.8-7.4	7.3	cSt
Viscosity Index	ASTM D2270	≥ 160	162	
Flash Point	ASTM D92	≥ 210	218	°C
Poor Point	ASTM D5950	≤ -40	-40	°C
Brookfield @ -40°C & 12.0 RPM	ASTM D2983	≤ 18000	17700	cP