



ATF M1375.4



LOREX ATF M1375.4 Fluid is a full synthetic lubricant based on carefully selected very high quality base oils that have been specially developed for ZF 6-speed series transmissions of ZF 6HP19, 6HP21, 6HP26, 6HP28, 6HP32, 6HP34. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

RECOMMENDATIONS:

BMW: 8322 0142516/ 8322 0144137

ZF S671 090252/ 253

ZF TE-ML 11

JAGUAR: 8432/ LAND ROVER TYK500050

AUDI/ VW: G 055005 A1/ A2/ A6

Hyundai & KIA: 04500-00115/ 040000C90SG



CERTIFICATE OF ANALYSIS

TEST	METHODS	SPECIFICATIONS	RESULT	UNITS
Appearance	Visual	Clear	Clear	-
Color	ASTM D1500	Amber Yellow	Amber Yellow	-
Density @ 15°C	ASTM D4052	0.84≤	0.845	g/cm ³
Kinematic Viscosity @ 40°C	ASTM D445	26.0 - 30.0	27.9	cSt
Kinematic Viscosity @ 100°C	ASTM D445	6.0-6.4	6.0	cSt
Viscosity Index	ASTM D2270	170≤	179	°C
Flash Point	ASTM D92	220≤	226	°C
Pour Point	ASTM D5950	-40≥	-44	cP
Brookfield @ -40°C & 12.0 RPM	ASTM D2983	12000≥	10500	cP