

## ATF SP-III



**LOREX ATF SP-III Fluid** is universal ATF for 4HP automatic transmission of Mitsubishi, Hyundai and Kia.

### RECOMMENDATIONS:

HYUNDAI & KIA ATF SP-III, SP-3  
HYUNDAI 04500-00100  
HYUNDAI 04500-00400  
HYUNDAI 04500-00A00  
HYUNDAI 00232-19012  
KIA JWS 3313  
MITSUBISHI 4024401, 4024610  
MITSUBISHI MZ320159/ 160/ 162/ 216



### CERTIFICATE OF ANALYSIS

TEST	METHODS	SPECIFICATIONS	RESULT	UNITS
Appearance	Visual	Clear	Clear	-
Color	ASTM D1500	Red	Red	-
Density @ 15°C	ASTM D4052	≥ 0.84	0.848	g/cm <sup>3</sup>
Kinematic Viscosity @ 40°C	ASTM D445	28.0 - 34.0	34	cSt
Kinematic Viscosity @ 100°C	ASTM D445	≥ 7.0	7.4	cSt
Viscosity Index	ASTM D2270	≥ 160	160	
Flash Point	ASTM D92	≥ 210	220	°C
Poor Point	ASTM D5950	≤ -40	-40	°C
Brookfield @ -40°C & 12.0 RPM	ASTM D2983	≤ 18000	17100	cP